

## **NUMBER: VNMT20006899**





### **TEST REPORT**

NUMBER: VNMT20006899 DATE: 27-Feb-2020

APPLICANT : CONG TY TNHH-SX-TM-DV THAO MINH

2977/11 HIGHWAY 1A, SECTOR 5, TAN THOI NHAT WARD,

DISTRICT 12, HO CHI MINH, VIET NAM

ATTN : KHUONG

Sample Description As Declared : Face Mask Color : White

No. of Sample : 2 Pieces + Fabric

Order No./PO No. : Buyer Name : Style No. : Fiber Content : Article No. : -

Date Received/Date Test Started : 25 Feb 2020

Date Confirmation Received : -

TEST CONDUCTED: AS PER THE REQUEST OF THE APPLICANT. FOR FURTHER DETAILS PLEASE REFER TO ENCLOSED PAGE(S)

**AUTHORIZED BY** 

FOR INTERTEK VIETNAM LTD. [HO CHI MINH]

PHUONG LE

SOFTLINES GENERAL MANAGER

(THIS REPORT SHALL NOT BE REPRODUCED WHOLLY OR IN PARTS WITHOUT WRITTEN APPROVAL FROM THE LABORATORY)



## **TEST REPORT**

NUMBER: VNMT20006899 DATE: 27-Feb-2020

TEST CONDUCTED (AS REQUESTED BY THE APPLICANT)

# 1. Water Repellency - As Received

ISO 4920 - 2012

Rating 4.5\*

**REMARK:** 

## 2. Transmittance or Blocking of Erythemally Weighted Ultraviolet Radiation Through Fabric

AATCC 183 - 2014, ASTM D6603-2019 (As Received Only)

- Solar Spectrum Irradiance Used: Noonday, July 3, Sunlight, Albuquerque
- Instrument Used: UV-2000FWavelength Resolution: 2 nm
- No. of Scan: 6

|                                 | Shell           |                        |
|---------------------------------|-----------------|------------------------|
|                                 | <u>Dry</u>      | <u>Wet</u>             |
| The Mean Ultraviolet Protection | 24.0            | 28.23                  |
| Factor, UPF                     |                 |                        |
| The UV-A Transmittance, T(UV-   | 6.19%           | 5.88%                  |
| A)                              |                 |                        |
| The UV-B Transmittance, T(UV-B) | 3.58%           | 2.94%                  |
| The Percent Blocking (UV-A)     | 93.81%          | 94.12%                 |
| The Percent Blocking (UV-B)     | 96.42%          | 97.06%                 |
| UPF Rating For Label            | 20              | 20                     |
| UVR Protection Category         | Good Protection | <b>Good Protection</b> |
|                                 |                 |                        |
|                                 | Lining          |                        |
|                                 | <u>Dry</u>      | <u>Wet</u>             |
| The Mean Ultraviolet Protection | 71.15           | 21.94                  |
| Factor, UPF                     |                 |                        |
| The UV-A Transmittance, T(UV-   | 0.90%           | 1.99%                  |
| A)                              |                 |                        |
| The UV-B Transmittance, T(UV-B) | 1.16%           | 3.61%                  |
| The Percent Blocking (UV-A)     | 99.10%          | 98.01%                 |
| The Percent Blocking (UV-B)     | 98.84%          | 96.39%                 |
| UPF Rating For Label            | 20              | 20                     |
| UVR Protection Category         | Good Protection | Good Protection        |
|                                 |                 |                        |

## END OF THE TEST REPORT ##

<sup>\*</sup>Water Penetration Through From Face To Back (Shell Fabric)



## **TEST REPORT**

NUMBER: VNMT20006899 DATE: 27-Feb-2020

This report (including any enclosures and attachments) are prepared for the exclusive use of the Customer(s) named in the report and solely for the purpose for which it is provided and on the basis of instructions and information and/or materials supplied by Intertek's Customer. The test results relate only to the specific items tested and are not intended to be a recommendation for any particular course of action. Customer is responsible for acting as it sees fit on the basis of such results. Unless Intertek provide express prior written consent, no part of this report should be reproduced, distributed or communicated to any third party. Intertek do not accept any liability if this report is used for an alternative purpose from which it is intended, nor do Intertek owe any duty of care to any third party in respect of this report. Except where explicitly agreed in writing, all work and services performed is governed by Intertek Standard Terms and Conditions of Service which is available on request or can be obtained at http://www.intertek.com/terms.